

TECO Westinghouse

ISSUED 8/6/2019	PERFORMANCE DATA 3-PHASE PERMANENT MAGNET MOTOR	ENCLOSURE TEFC
TYPE DVEM		CATALOG# DM0014

NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	TIME RATING	SERVICE FACTOR
HP	KW								
1	0.75	6	143T	460	90	40°C	F	CONT.	1

VARIABLE FREQUENCY DRIVE SERVICE

VARIABLE TORQUE				OHMS/PHASE EQUIVALENT WYE CIRCUIT (AT RATED OPERATING TEMPERATURE 25°C)			
HZ	HP	RPM	TORQUE (lb-ft)	RESIST.	Ld	Lq	BEMF
9~90	0.06~1	180~1800	1.76~2.90	13.604 Ω	35.16 mH	62.23 mH	171 mV/rpm

CONSTANT TORQUE				CONSTANT HORSEPOWER			
HZ	HP	RPM	TORQUE (lb-ft)	HZ	HP	RPM	TORQUE (lb-ft)
60~90	0.67~1	1200~1800	2.90	90~135	1	1800~2700	2.90~1.95

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY			POWER FACTOR			SOUND PRESSURE LEVEL @ 3 FT Db(A)
	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	
1800	85.7	85.7	85.2	99.2	99.6	99.3	63

CURRENTS		TORQUE		INERTIA
NO LOAD (A)		FULL LOAD (A)		ROTOR WR2 (lb-ft ²)
0.20		1.50		0.035

APPROVED:	M. PRATER	DRAWING NO.	31057DM0014	REVISION:	1
-----------	------------------	-------------	--------------------	-----------	----------