

TECO Westinghouse

ISSUED 8/6/2019	PERFORMANCE DATA 3-PHASE PERMANENT MAGNET MOTOR	ENCLOSURE TEFC
TYPE DVEM		CATALOG# DM0254

NAMEPLATE INFORMATION

OUTPUT		POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	TIME RATING	SERVICE FACTOR
HP	KW								
25	18.5	6	284T	460	90	40°C	F	CONT.	1

VARIABLE FREQUENCY DRIVE SERVICE

VARIABLE TORQUE				OHMS/PHASE EQUIVALENT WYE CIRCUIT (AT RATED OPERATING TEMPERATURE 25°C)			
HZ	HP	RPM	TORQUE (lb-ft)	RESIST.	Ld	Lq	BEMF
9~90	1.49~25	180~1800	43.4~72.4	0.238 Ω	4.44 mH	8.22 mH	195 mV/rpm

CONSTANT TORQUE				CONSTANT HORSEPOWER			
HZ	HP	RPM	TORQUE (lb-ft)	HZ	HP	RPM	TORQUE (lb-ft)
60~90	16.53~25	1200~1800	72.4	90~135	25	1800~2700	72.4~48.3

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY			POWER FACTOR			SOUND PRESSURE LEVEL @ 3 FT Db(A)
	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	FULL LOAD %	3/4 LOAD %	1/2 LOAD %	
1800	94.2	94.2	93.3	93.2	96.3	98.4	74

CURRENTS		TORQUE		INERTIA
NO LOAD (A)		FULL LOAD (A)		ROTOR WR2 (lb-ft ²)
0.90		33.00		1.258

APPROVED:	M. PRATER	DRAWING NO.	31057DM0254	REVISION:	1
-----------	------------------	-------------	--------------------	-----------	----------