

11

10

9

8

7

6

5

4


3

2

1

POLE	HP	kW	Hz	VOLT	r/min(RPM)	INS	RATING	DIMENSION IN	APPROX WEIGHT	BEARINGS
6	200	149	60	460	1200	F	CONT.	INCHES	2247lbs	DE: 6320 NDE: 6316

TOTALLY ENCLOSED FAN-COOLED TYPE. SQUIRREL-CAGE ROTOR



NOTE:
 1. FOR DIRECT FLEXIBLE COUPLING
 2. ENCLOSURE: IP54 PROTECTION

REMOVABLE COVER FOR CABLE ENTRY TO BE DRILLED BY THE CUSTOMER.

OUTLINE DIMENSIONS			
3-PHASE INDUCTION MOTOR			
MOTOR TYPE	AEHH8P	FRAME NO.	449T
CATALOG #	NP2006	DATE	MARCH, 10, 2020
ORDER NO.		TRANS. SHEET	

APPD.	BEN. YANG	04.08.19
CHKD.	K. L. KUO	04.08.19
DWG.	K. L. KUO	01.29.19

TEC Westinghouse

DWG NO.
31057C526031

06.13.19 Show approx weight K. L. KUO

11

10

9

8

7

6

5

4

3

2

1