




CATALOG #	ASHA	FRAME	OUTPUT		POLE	SYN. SPEED R.P.M.	VOLTAGE V.	Hz.	TIME RATING	INSULATION CLASS	SERVICE FACTOR	BEARINGS		WEIGHT LBS
			HP	kW								DE	NDE	
PG6008	AMHG	5810C	600	447.4	8	900	2300/4160	60	CONT.	F	1.15	NU326C3	6322	6600

WEATHER PROTECTED TYPE I. SQUIRREL CAGE ROTOR



- NOTES:
1. DIMENSIONS IN INCH.
 2. ENCLOSURE: IP23.
 3. FOR BELT DRIVE.
 4. SPACE HEATER RATED 120 VOLT, SINGLE PHASE.
 5. 100 OHM PLATINUM WINDING RTD'S, 2 PER PHASE.
 6. PROVISION FOR BEARING RTD MOUNTING:
2X .50" NPT PER BRACKET.

REF.	REV. DATA	TECO Westinghouse		REV NO
		3-PHASE INDUCTION MOTOR OUTLINE DIMENSIONS		01
4B040L332	DWN K. MILNER	071817	APPD T. FELPS	071817
	TECO-WESTINGHOUSE MOTOR COMPANY			
	ROUND ROCK, TEXAS USA			