



TYPE	OUTPUT		POLE	TIME RATING	VOLTAGE V	Hz	SYN. SPEED R.P.M
	HP.	kW.					
AEHHXU	150	111.8	2	CONT.	460	60	3600

TOTALLY ENCLOSED FAN-COOLED TYPE . SQUIRREL-CAGE ROTOR



NOTE :

1. DIMENSIONS IN INCHES
2. FRAME NO. 445TS
3. F CLASS INSULATION
4. FOR DIRECT FLEXIBLE COUPLING
5. ENCLOSURE: IP55
6. UL EXPLOSION PROOF
7. NON-SPARKING FAN
8. BEARING SIZE: DRIVE-END 6313C3  
OPP. DRIVE-END 6313C3
9. CLASS I, DIVISION 1, GROUP D AND CLASS II, GROUPS E, F AND G TEMP CODE T2D/T3B.

DATE DEC 08 2016

OUTLINE DIMENSIONS

XP1502

3-PHASE INDUCTION MOTOR

DWN.	H. CHEN	DEC. 21. 2010
CHKD.	W. WENG	DEC. 21. 2010
APPD.	T. HSIAO	DEC. 21. 2010

TEC Westinghouse

DWG NO. REV: 00

3A049DTA10108-52