TECO Westinghouse

ISSUED	PERFORMANCE DATA	ENCLOSURE
December 16, 2005	3-PHASE INDUCTION MOTOR	TEFC
TYPE: AEHH		CATALOG#: HH0034-50

NAMEPLATE INFORMATION

OUTPUT HP	OUTPUT KW	POLE	FRAME SIZE	VOLTAGE	HZ	RATED AMBIENT	INS. CLASS	NEMA DESIGN	TIME RATING	SERVICE FACTOR
3	2.2	4	182T	380	50	40°C	F	B	CONT.	1.00

TYPICAL PERFORMANCE

FULL LOAD RPM	EFFICIENCY FULL LOAD MIN. %	EFFICIENCY FULL LOAD NOM. %	EFFICIENCY 3/4 LOAD %	EFFICIENCY 1/2 LOAD %	POWER FACTOR F. L. %	POWER FACTOR 3/4 LOAD %	POWER FACTOR 1/2 LOAD %	MAXIMUM POWER FACTOR CORRECTION
1430	84	86.5	88.5	88.5	89.5	88	81.5	1 KVAR

CURRENTS NO LOAD AT 380 VOLT	CURRENTS FULL LOAD AT 380 VOLT	CURRENTS LOCKED ROTOR AT 380 VOLT	NEMA KVA CODE LETTER
1.36	4.39	43.00	K

TORQUE FULL LOAD lb-ft	TORQUE LOCKED ROTOR %FLT	TORQUE PULL UP %FLT	TORQUE BREAK DOWN %FLT	INERTIA ROTOR WR^2 $lb\text{-}ft^2$	INERTIA NEMA LOAD WK^2 $lb\text{-}ft^2$	INERTIA MAX ALLOWABLE WK^2 $lb\text{-}ft^2$	ACCEL TIME NEMA LOAD WK^2 Sec	ACCEL TIME MAX ALLOWABLE WK^2 Sec
11.01	155	145	250	0.404	25.5832	81.42857143	5.67	17.85

SAFE STALL TIME IN SECONDS COLD	SAFE STALL TIME IN SECONDS HOT	ALLOWABLE STARTS PER HOUR COLD	ALLOWABLE STARTS PER HOUR HOT	SOUND PRESSURE LEVEL @ 3 FT dB(A)
36	25	2	1	52

APPROVED:	M. PRATER	DRAWING NO.	31057HH0034	REVISION 0